



**AROK-TRADE d.o.o.**  
www.aroktrade.com

24400 Senta  
Tel/fax: 024/812-221  
Mobil: 063/733 77 76  
e-mail: office@aroktrade.com  
PIB: 103418525  
TR: 170-30008811000-43 Unicredit Banka  
TR: 265-2420310000041-19 Raiffeisen Banka

**PHVPHK-SERIA: od 2 do 15 kw  
Tehn.podaci:**

Kod	Modell	Sabijač	Kapacitet		Snaga		V/F/Hz	Priklj.	Pritisak	Težina	Rez.	Bučnost	Dimenzije	
Codice Code	Modello	Gruppo Vite	L/T'	m <sup>3</sup> /h	HP	kW		connes.	PSI bar	kg	L	dB(A)	ArBxC	
<b>MODELLO PHV S 270 CON SERBATOIO ED ESSICCATORE/ MODEL PHV S 270 WITH TANK AND DRYER</b>														
1612130330	PHV3S270E/EC06-08	V60	360	21,4	3,0	2,2	400/3/50	1/2"	116	8	226	270	62	150x60x151
1612130340	PHV3S270E/EC06-10	V60	310	18,4	3,0	2,2	400/3/50	1/2"	145	10	226	270	62	150x60x151
1612130350	PHV4S270E/EC06-08	V60	420	24,9	4,0	3	400/3/50	1/2"	116	8	227	270	62	150x60x151
1612130360	PHV4S270E/EC06-10	V60	390	23,1	4,0	3	400/3/50	1/2"	145	10	227	270	62	150x60x151
1612130370	PHV5.5S270E/EC06-08	V60	600	35,6	5,5	4	400/3/50	1/2"	116	8	231	270	64	150x60x151
1612130380	PHV5.5S270E/EC06-10	V60	540	32,0	5,5	4	400/3/50	1/2"	145	10	231	270	64	150x60x151
1612130390	PHV5.5S300E/EC06-13	V60	440	26,1	5,5	4	400/3/50	1/2"	188	13	241	300	64	150x60x151
1612130400	PHV7.5S270E/EC06-08	V60	820	48,7	7,5	5,5	400/3/50	1/2"	116	8	244	270	67	150x60x151
1612130410	PHV7.5S270E/EC06-10	V60	780	45,1	7,5	5,5	400/3/50	1/2"	145	10	244	270	67	150x60x151
1612130420	PHV7.5S300E/EC06-13	V60	650	38,6	7,5	5,5	400/3/50	1/2"	188	13	254	300	67	150x60x151
1612130430	PHV10S270E/EC06-08	V60	950	56,4	10,0	7,5	400/3/50	1/2"	116	8	246	270	69	150x60x151
1612130440	PHV10S270E/EC06-10	V60	900	53,4	10,0	7,5	400/3/50	1/2"	145	10	246	270	69	150x60x151
1612130450	PHV10S300E/EC06-13	V60	770	45,7	10,0	7,5	400/3/50	1/2"	188	13	256	300	69	150x60x151
<b>MODELLO PHV S 500 CON SERBATOIO ED ESSICCATORE/ MODEL PHV S 500 WITH TANK AND DRYER</b>														
1612130460	PHV7.5S500E/EC06-08	V60	820	48,7	7,5	5,5	400/3/50	1/2"	116	8	306	500	67	192x60x165
1612130470	PHV7.5S500E/EC06-10	V60	760	45,1	7,5	5,5	400/3/50	1/2"	145	10	306	500	67	192x60x165
1612130480	PHV7.5S500E/EC06-13	V60	650	38,6	7,5	5,5	400/3/50	1/2"	188	13	316	500	67	192x60x165
1612130490	PHV10S500E/EC06-08	V60	950	56,4	10,0	7,5	400/3/50	1/2"	116	8	308	500	69	192x60x165
1612130500	PHV10S500E/EC06-10	V60	900	53,4	10,0	7,5	400/3/50	1/2"	145	10	308	500	69	192x60x165
1612130510	PHV10S500E/EC06-13	V60	770	45,7	10,0	7,5	400/3/50	1/2"	188	13	318	500	69	192x60x165

**oprema:**



kompresorski vijčani elemenat sa ubrizgavanjem ulja marke **SCA 8-VMC(IT)**, električni motor (400V;3F;50Hz;IP55) sa klasom izolacije F, kaišni pogon, sa automatskim odvajačem vlage, ugrađen automatski sistem za regulaciju kapaciteta (princip: puno opterećenje / prazan hod-start-stop), M-06 inteligentan el. upravljač-LOGIKA (IT) usisni ventil sa filterom za vazduh, vazdušno hladni kombinovani hladnjak za ulje i za komprimirani vazduh prekidač pritiska, ugrađeni električni orman sa IP54 izolacijom, **EPS2(Siemens)** el. +upravljanje, instrumenti za merenje temperatura ulja, pritiska, pokazivač servisnih funkcija (zamenja filter elemenata-za vazduh i separatora ulja) zaštita prilikom niskog nivoa ulja, termostat ulja, zaštita električnog motora, sigurnosni ventil, nepovrati ventil, moderno oblikovani izolacioni i zaštitni poklopac. brojač sati, merač pritiska, usisni filter, merač temp. ulja, kombinovani hladnjak ulja i vazduha (zadnji)

**Po mogućnosti sa sušačem ili sa rezervorom od 270lit.-do 500 lit**



**AROK-TRADE d.o.o.**  
www.aroktrade.com

24400 Senta  
Tel/fax: 024/812-221  
Mobil: 063/733 77 76  
e-mail: office@aroktrade.com  
PIB: 103418525  
TR: 170-30008811000-43 Unicredit Banka  
TR: 265-2420310000041-19 Raiffeisen Banka

**MODELLO / MODEL PHK**

1612130520	PHK10/EC06-08	V75	1160	68,8	10,0	7,5	400/3/50	3/4"	116	8	217	-	65	92x60x96
1612130530	PHK10/EC06-10	V75	1050	62,3	10,0	7,5	400/3/50	3/4"	145	10	217	-	65	92x60x96
1612130540	PHK10/EC06-13	V75	800	47,5	10,0	7,5	400/3/50	3/4"	188	13	217	-	65	92x60x96
1612130550	PHK15/EC06-08	V75	1850	109,8	15,0	11	400/3/50	3/4"	116	8	237	-	68	92x60x96
1612130560	PHK15/EC06-10	V75	1550	92,0	15,0	11	400/3/50	3/4"	145	10	237	-	68	92x60x96
1612130570	PHK15/EC06-13	V75	1350	80,1	15,0	11	400/3/50	3/4"	188	13	237	-	68	92x60x96
1612130580	PHK20/EC06-08	V75	2350	139,5	20,0	15	400/3/50	3/4"	116	8	243	-	70	92x60x96
1612130590	PHK20/EC06-10	V75	2100	124,6	20,0	15	400/3/50	3/4"	145	10	243	-	70	92x60x96
1612130600	PHK20/EC06-13	V75	1600	95,0	20,0	15	400/3/50	3/4"	188	13	243	-	70	92x60x96

**MODELLO PHK S 270 CON SERBATOIO 270 LT / MODEL PHK S 270 WITH 270 LT TANK**

1612130610	PHK10S270/EC06-08	V75	1160	68,8	10,0	7,5	400/3/50	1/2"	116	8	277	270	65	157x60x150
1612130620	PHK10S270/EC06-10	V75	1050	62,3	10,0	7,5	400/3/50	1/2"	145	10	277	270	65	157x60x150
1612130630	PHK10S300/EC06-13	V75	800	47,5	10,0	7,5	400/3/50	1/2"	188	13	287	300	65	173x60x150
1612130640	PHK15S270/EC06-08	V75	1850	109,8	15,0	11	400/3/50	1/2"	116	8	297	270	68	157x60x150
1612130650	PHK15S270/EC06-10	V75	1550	92,0	15,0	11	400/3/50	1/2"	145	10	297	270	68	157x60x150
1612130660	PHK15S300/EC06-13	V75	1350	80,1	15,0	11	400/3/50	1/2"	188	13	307	300	68	173x60x150
1612130670	PHK20S270/EC06-08	V75	2350	139,5	20,0	15	400/3/50	1/2"	116	8	303	270	70	157x60x150
1612130680	PHK20S270/EC06-10	V75	2100	124,6	20,0	15	400/3/50	1/2"	145	10	303	270	70	157x60x150
1612130690	PHK20S300/EC06-13	V75	1600	95,0	20,0	15	400/3/50	1/2"	188	13	313	300	70	173x60x150

**MODELLO PHK S 500 CON SERBATOIO 500 LT / MODEL PHK S 500 WITH 500 LT TANK**

1612130700	PHK10S500/EC06-08	V75	1160	68,8	10,0	7,5	400/3/50	3/4"	116	8	339	500	65	196x60x158
1612130710	PHK10S500/EC06-10	V75	1050	62,3	10,0	7,5	400/3/50	3/4"	145	10	339	500	65	196x60x158
1612130720	PHK10S500/EC06-13	V75	800	47,5	10,0	7,5	400/3/50	3/4"	188	13	349	500	65	196x60x158
1612130730	PHK15S500/EC06-08	V75	1850	109,8	15,0	11	400/3/50	3/4"	116	8	359	500	68	196x60x158
1612130740	PHK15S500/EC06-10	V75	1550	92,0	15,0	11	400/3/50	3/4"	145	10	359	500	68	196x60x158
1612130750	PHK15S500/EC06-13	V75	1350	80,1	15,0	11	400/3/50	3/4"	188	13	369	500	68	196x60x158
1612130760	PHK20S500/EC06-08	V75	2350	139,5	20,0	15	400/3/50	3/4"	116	8	365	500	70	196x60x158
1612130770	PHK20S500/EC06-10	V75	2100	124,6	20,0	15	400/3/50	3/4"	145	10	365	500	70	196x60x158
1612130780	PHK20S500/EC06-13	V75	1600	95,0	20,0	15	400/3/50	3/4"	188	13	375	500	70	196x60x158

\*ISO 1217

**oprema:**



kompresorski vijčani elemenat sa ubrizgavanjem ulja marke **SCA 8-VMC(IT)**, električni motor (**400V;3F;50Hz;IP55**) sa klasom izolacije F, kaišni pogon, sa automatskim odvajačem vlage, ugrađen automatski sistem za regulaciju kapaciteta (princip: puno opterećenje / prazan hod-start-stop), M-06 inteligentan el. upravljač-LOGIKA (IT) usisni ventil sa filterom za vazduh, vazdušno hladni kombinovani hladnjak za ulje i za komprimirani vazduh prekidač pritiska, ugrađeni električni orman sa IP54 izolacijom, **EPS2(Siemens)** el. +upravljanje, instrumenti za merenje temperatura ulja, pritiska, pokazivač servisnih funkcija (zamena filter elemenata-za vazduh i separatora ulja) zaštita prilikom niskog nivoa ulja, termostat ulja, zaštita električnog motora, sigurnosni ventil, nepovrati ventil, moderno oblikovani izolacioni i zaštitni poklopac. brojač sati, merač pritiska, usisni filter, merač temp. ulja, kombinovani hladnjak ulja i vazduha (zadnji)

Po mogućnosti sa sušačem ili sa rezervorom od 270lit.-do 500 lit