



**AROK-TRADE d.o.o.**

www.aroktrade.com

24400 Senta  
Tel./fax 024/812-221  
Mobil.: 063/733 77 76  
Mobil.:063/74 66 147  
e-mail: aroktam@neobee.net  
PIB:103418525

TR:160-924747-35 Banca Intesa  
TR:220-32277-67 ProCredit Banka  
TR:265-242031000041-19 Raiffeisen Banka

## WIND 2÷15 serija

Tehn. Podaci:

	kW	V/ph/Hz	Bar	PSIG	l/min	m <sup>3</sup> /h	CFM	Model	dB(A)	l	Kg	cm
WIND 2-M	2.2	230/1/50	10	145	280	16.8	9.9	-	66	-	150	90x90x85
WIND 2	2.2	400/3/50	10	145	280	16.8	9.9	-	66	-	150	90x90x85
WIND 3	3.0	400/3/50	10	145	410	24.6	14.5	-	68	-	155	90x90x85
WIND 4	4.0	400/3/50	10	145	560	33.6	19.8	-	68	-	160	90x90x85
WIND 5	5.5	400/3/50	10	145	720	43.2	25.5	-	68	-	170	90x90x85
WIND 7	7.5	400/3/50	10	145	1000	60.0	35.0	-	70	-	190	90x90x85
WIND 11	11	400/3/50	10	145	1600	96.0	57.0	-	72	-	190	90x90x85
WIND 15	15	400/3/50	10	145	2000	120.0	70.6	-	74	-	195	90x90x85
WIND 2-M-270	2.2	230/1/50	10	145	280	16.8	9.9	-	66	270	230	155x90x145
WIND 2-270	2.2	400/3/50	10	145	280	16.8	9.9	-	66	270	230	155x90x145
WIND 3-270	3.0	400/3/50	10	145	410	24.6	14.5	-	68	270	235	155x90x145
WIND 4-270	4.0	400/3/50	10	145	560	33.6	19.8	-	68	270	240	155x90x145
WIND 5-270	5.5	400/3/50	10	145	720	43.2	25.5	-	68	270	250	155x90x145
WIND 7-270	7.5	400/3/50	10	145	1000	60.0	35.0	-	70	270	260	155x90x145
WIND 11-270	11	400/3/50	10	145	1600	96.0	57.0	-	72	270	270	155x90x145
WIND 15-500	15	400/3/50	10	145	2000	120.0	70.6	-	74	270	275	155x90x145
WIND 2-M-500	2.2	230/1/50	10	145	280	16.8	9.9	-	66	500	323	190x90x152
WIND 2-500	2.2	400/3/50	10	145	280	16.8	9.9	-	66	500	323	190x90x152
WIND 3-500	3.0	400/3/50	10	145	410	24.6	14.5	-	68	500	333	190x90x152
WIND 4 500	4.0	400/3/50	10	145	560	33.6	19.8	-	68	500	333	190x90x152
WIND 5-500	5.5	400/3/50	10	145	720	43.2	25.5	-	68	500	343	190x90x152
WIND 7-500	7.5	400/3/50	10	145	1000	60.0	35.0	-	70	500	353	190x90x152
WIND 11-500	11	400/3/50	10	145	1600	96.0	57.0	-	72	500	363	190x90x152
WIND 15-500	15	400/3/50	10	145	2000	120.0	70.6	-	74	500	368	190x90x152
WIND 2-M-270D	2.2	230/1/50	10	145	280	16.8	9.9	DE006	66	270	270	155x90x145
WIND 2-270 D	2.2	400/3/50	10	145	280	16.8	9.9	DE006	66	270	270	155x90x145
WIND 3-270D	3.0	400/3/50	10	145	410	24.6	14.5	DE006	68	270	275	155x90x145
WIND 4-270D	4.0	400/3/50	10	145	560	33.6	19.8	DE006	68	270	280	155x90x145
WIND 5-270D	5.5	400/3/50	10	145	720	43.2	25.5	DE009	68	270	290	155x90x145
WIND 7-270D	7.5	400/3/50	10	145	1000	60.0	35.0	DE009	70	270	300	155x90x145
WIND 11-270D	11	400/3/50	10	145	1600	96.0	57.0	DE012	72	270	310	155x90x145
WIND 15-270D	15	400/3/50	10	145	2000	120.0	70.6	DE018	74	270	315	155x90x145
WIND 2-M-500D	2.2	230/1/50	10	145	280	16.8	9.9	DE006	66	500	363	190x90x152
WIND 2-500D	2.2	400/3/50	10	145	280	16.8	9.9	DE006	66	500	363	190x90x152
WIND 3 500D	3.0	400/3/50	10	145	410	24.6	14.5	DE006	68	500	368	190x90x152
WIND 4 500D	4.0	400/3/50	10	145	560	33.6	19.8	DE006	68	500	373	190x90x152
WIND 5 500D	5.5	400/3/50	10	145	720	43.2	25.5	DE009	68	500	383	190x90x152
WIND 7 500D	7.5	400/3/50	10	145	1000	60.0	35.0	DE009	70	500	393	190x90x152
WIND 11 500D	11	400/3/50	10	145	1600	96.0	57.0	DE012	72	500	403	190x90x152
WIND 15 500D	15	400/3/50	10	145	2000	120.0	70.6	DE018	74	500	408	190x90x152

\*ISO 1217

### OPREMA:

kompresorski vijčani elemenat sa ubrizgavanjem ulja marke **GHH-Rand**, električni motor (**400V; 3F; 50Hz; IP55**) sa klasom izolacije F, kaišni pogon, sa automatskim odvajanjem vlage, ugrađen automatski sistem za regulaciju kapaciteta (princip: puno opterećenje/prazan hod–start-stop), M-06 inteligentan el. upravljač usisni ventil sa filterom za vazduh, vazdušno hladeni kombinovani hladnjak za ulje i za komprimirani vazduh prekidač pritiska, ugrađeni električni orman sa IP54 izolacijom, **EPS2 (Siemens)** el.





**AROK-TRADE d.o.o.**

[www.aroktrade.com](http://www.aroktrade.com)

24400 Senta  
Tel./fax 024/812-221  
Mobil.: 063/733 77 76  
Mobil.:063/74 66 147  
e-mail: [aroktam@neobee.net](mailto:aroktam@neobee.net)  
PIB:103418525  
TR:160-924747-35 Banca Intesa  
TR:220-32277-67 ProCredit Banka  
TR:265-242031000041-19 Raiffeisen Banka

+ upravljanje, instrumenti za merenje temperatura ulja, pritiska, pokazivač servisnih funkcija (zamena filter elemenata-za vazduh i separatora ulja) zaštita prilikom niskog nivoa ulja, termostat ulja, zaštita električnog motora, sigurnosni ventil, nepovrati ventil, moderno oblikovani izolacioni i zaštitni poklopac. brojač sati, merač pritiska, usisni filter, merač temp. ulja, kombinovani hladnjak ulja i vazduha (zadnji)

**Po mogućnosti sa sušačem ili sa rezervorom od 270lit.**